

# BETASEAL™ 43533

## Body Primer

### Description

**BETASEAL™ 43533** is a methylene chloride-free, polyurethane based, solvent release type primer suitable for use to promote adhesion between Betaseal Urethane Adhesives and enamel topcoats.

### Typical Applications

**BETASEAL 43533** primer is an integral component of a **BETASEAL** bonding system. It is used for priming coated automotive body flanges (pinchwelds) before the application of a **BETASEAL** adhesive.

### Application Techniques

The primer may be applied by pressurized flow gun, brush, or other suitable applicator. Provided the primed surface is kept clean, sealant may be applied within 110 hours. Allow **BETASEAL 43533** to dry at least 30 minutes prior to application of the **BETASEAL** adhesive.

### Safety Precautions

Refer to Material Safety Data Sheet for details.

### Storage

**BETASEAL 43533** Primer is a moisture sensitive material and **MUST** be stored in airtight, dry containers at temperatures between 65° and 95°F.

### Storage Stability

Shelf stability is assured for 6 months from date of manufacture when stored according to manufacturer's instructions.

### Packaging

**BETASEAL 43533** is available in 150ml, 275ml and one-quart bottles. It is also in 5-gallon pails.

### Physical Properties

<b>Appearance</b>	Clear
VOC lbs./gl	4.90
<b>Flash Point,</b>	
°F	15°
°C	-9°
<b>Solids Content,</b>	
minimum, %	39
<b>Viscosity, Ford Cup # 4</b>	12-16

**Contact your Dow Automotive Sales Representative for more detailed information.**

### DISCLAIMER OF WARRANTY

All statements, technical information and recommendations herein are based on tests we believe to be reliable. **BUT THE ACCURACY OR COMPLETENESS THEREOF IS NOT GUARANTEED, AND THE FOLLOWING IS MADE IN LIEU OF ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR PURPOSE.** Seller's and manufacturers only obligation shall be to replace such quantity of the product proved to be defective. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therein. **NEITHER SELLER NOR MANUFACTURER SHALL BE LIABLE EITHER IN CONTRACT FOR ANY LOSS OR DAMAGE, DIRECT, INCIDENTAL, OR CONSEQUENTIAL, ARISING OUT OF THE USE AND OR THE INABILITY TO USE THE PRODUCT.** No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacturer.