



BETASEAL™ 43555

PVC Primer

Description

BETASEAL™ 43555 PVC Primer is designed to promote adhesion between BETASEAL adhesives and PVC substrates.

Typical Applications

BETASEAL 43555 PVC Primer is used in conjunction with Betaseal Adhesives for bonding automotive vinyl trim to glass and various painted substrates.

Application Techniques

BETASEAL 43555 can be applied to the PVC using a small paintbrush, spray equipment, or other suitable applicator. Air-dry the primer for a minimum of 3 minutes prior to applying a BETASEAL adhesive. On many PVC surfaces the dry primer can usually be allowed to remain open for up to 3 months before recoating becomes necessary. (Different PVC's, however, may exhibit various open times that should be tested on an individual basis.)

Safety Precautions

Refer to Material Safety Data Sheet for details.

Storage

BETASEAL 43555 PVC Primer is a moisture sensitive material and MUST be stored in airtight, dry containers at temperatures between 65° and 95°F. **Do not store outside.**

Storage Stability

Shelf stability is assured for 6 months from date of manufacture when stored according to manufacturer's instructions.

Clean- Up

To clean equipment, use Urethane E* Sealant Cleaner. For cleaning hands, use Urethane E* Industrial Hand Cleaner.

Packaging

BETASEAL 43555 is available in one-quart and 125ml bottles. It is also available in 5-gallon pails.

Physical Properties

Appearance	Amber
VOC lbs./gl	5.90
Flash Point,	
°F	24°
°C	-4°
Solids Content,	
minimum, %	17.5
Viscosity, # 2 Zahn	17-24

Contact your Dow Automotive Sales Representative for more detailed information.

DISCLAIMER OF WARRANTY

All statements, technical information and recommendations herein are based on tests we believe to be reliable. BUT THE ACCURACY OR COMPLETENESS THEREOF IS NOT GUARANTEED, AND THE FOLLOWING IS MADE IN LIEU OF ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR PURPOSE. Seller's and manufacturers only obligation shall be to replace such quantity of the product proved to be defective. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therein. NEITHER SELLER NOR MANUFACTURER SHALL BE LIABLE EITHER IN CONTRACT FOR ANY LOSS OR DAMAGE, DIRECT, INCIDENTAL, OR CONSEQUENTIAL, ARISING OUT OF THE USE AND OR THE INABILITY TO USE THE PRODUCT. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacturer.