

# BETASEAL™ 43518

## Glass Primer

### Description

**BETASEAL™ 43518 Glass Primer** is a solvent based silane blend type primer. It is used to condition the surface and promote adhesion to glass. This primer is used in conjunction with an approved blackout glass primer and polyurethane adhesive.

### Typical Applications

As an integral component of a BETASEAL™ bonding system, BETASEAL™ 43518 is used to condition glass surfaces, such as windshields and backlites of automobiles, trucks, buses and off-road vehicles.

### Application Techniques

BETASEAL™ 43518 may be applied by means of a brush or other suitable applicator. After application, wipe with a clean lint free cloth, leaving a thin layer of primer. If blackout primer or related material is not applied within 10 minutes, prime and wipe must be repeated.

### Safety Precautions

Refer to Material Safety Data Sheet for details.

### Storage

BETASEAL™ 43518 primer is a moisture-sensitive material and **MUST** be stored in air tight, dry containers at temperatures between 18°C (65°F) and 35°C (95°F).

### Storage Stability

Shelf stability is assured for 6 months from date of manufacture when stored according to manufacturer's instructions. Urethane adhesives and primers are marked with expiration dates.

### Packaging

BETASEAL 43518 is available in one-liter cans and 150ml bottles.

### Physical Properties

Appearance	Clear
VOC, kg/L	0.83
Flash Point, °F	27°
°C	-3°
Viscosity, # 1 Zahn, seconds	29-34

**Contact your Dow Automotive Sales Representative for more detailed information.**

### DISCLAIMER OF WARRANTY

All statements, technical information and recommendations herein are based on tests we believe to be reliable. **BUT THE ACCURACY OR COMPLETENESS THEREOF IS NOT GUARANTEED, AND THE FOLLOWING IS MADE IN LIEU OF ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR PURPOSE.** Seller's and manufacturers only obligation shall be to replace such quantity of the product proved to be defective. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therein. **NEITHER SELLER NOR MANUFACTURER SHALL BE LIABLE EITHER IN CONTRACT FOR ANY LOSS OR DAMAGE, DIRECT, INCIDENTAL, OR CONSEQUENTIAL, ARISING OUT OF THE USE AND OR THE INABILITY TO USE THE PRODUCT.** No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacturer.

