

LUSTRAN[®] ABS LK197

ABS

Extrusion Grade

Description

Lustran ABS LK197 resin is a low-gel, high-gloss, medium-impact extrusion grade of ABS (Acrylonitrile Butadiene Styrene). It provides excellent surface appearance, a superior balance between rigidity and impact strength, and excellent melt strength for good thermoformability. It is easy to color with ABS color concentrates.

Applications

Lustran ABS LK197 resin is used in applications that require high gloss and higher rigidity, such as bathtubs, sinks, and shower surrounds for recreational vehicles, and interior liners for ice chests and picnic coolers. As with any product, use of Lustran ABS LK197 resin in a given application must be tested (including but not limited to field testing) in advance by the user to determine suitability.

Drying

Drying prior to processing is recommended in a desiccant dehumidifying hopper dryer. An inlet air dew point of -20°F (-29°C) or below is recommended to achieve a maximum moisture content of 0.03%. Typical drying conditions are 3–4 hours at 180°-200°F (82-93°C).

Processing

Extruder. To obtain an optimum balance of sheet gloss and mechanical properties, the extruder profile should be set to deliver polymers at a melt temperature between 420° and 480°F (215° and 249°C). A barrel temperature of 420°-465°F (215-240°C) is recommended.

Screw Design. Single- or two-stage screws can be used, although a two-stage screw is preferred. For two-stage screws, a first-stage compression ratio (feed depth to metering depth) of 2.5 – 2.7 and a pump ratio (second-stage metering to first-stage metering) of 1.5 – 2.0 are recommended.

Die. Die temperature settings for Lustran ABS normally range between 410° and 465°F (210° and 241°C). The die should be adjusted to provide uniform polymer melt at the lips.

Roll Stack. Suggested polishing roll settings for Lustran ABS using a standard S wrap are noted below. Specific settings are dependent on roll diameter, sheet gauge and linear speed.

Polishing Roll	Down Stack	Up Stack
Top	180°-220°F (82°-105°C)	180°-220°F (82-105°C)
Middle	145°-185°F (63°-85°C)	170°-210°F (77°-99°C)
Bottom	180°-220°F (82°-105°C)	160°-200°F (71°-93°C)

Additional information on processing may be obtained by contacting an INEOS ABS technical service representative.

Regrind Information

Where end-use requirements permit, up to 40% Lustran ABS resin regrind may be used with virgin material, provided that the material is kept free of contamination and is properly dried (see section on Drying). Only compatible materials should be used for regrind. Lustran ABS resin is totally compatible with Centrex[®] resin at all ratios. Other thermoplastics, such as polystyrene, polyethylene, and polypropylene, to mention a few, are not compatible, and mixing will result in appearance and property degradation.

Any regrind used must be generated from properly extruded and/or thermoformed parts and trim scrap. All regrind used must be clean, uncontaminated, and thoroughly blended with virgin resin prior to drying and processing. Under no circumstances should degraded, discolored, or contaminated material be used for regrind. Material of this type should be properly discarded.

Improperly mixed and/or dried regrind may diminish the desired properties of Lustran resin. It is critical that you test finished parts produced with any amount of regrind to ensure that your end-use performance requirements are fully met. Regulatory or testing organizations (e.g., UL) may have specific requirements limiting the allowable amount of regrind. Because third party regrind generally does not have a traceable heat history, or offer any assurance that proper temperatures, conditions, and/or materials were used in processing, extreme caution must be exercised in buying and using regrind from third parties.

The use of regrind material should be avoided entirely in those applications where resin properties equivalent to virgin material are required, including but not limited to color quality, impact strength, resin purity, and/or load-bearing performance.

Health and Safety Information

Appropriate literature has been assembled which provides information concerning the health and safety precautions that must be observed when handling the INEOS ABS products mentioned in this publication. For materials mentioned which are not INEOS ABS products, appropriate industrial hygiene and other safety precautions recommended by their manufacturers should be followed. Before working with any of these products, you must read and become familiar with the available information on their hazards, proper use, and handling. This cannot be overemphasized. Information is available in several forms, e.g., *material safety data sheets and product labels*. Consult your INEOS ABS representative or contact the Product Safety and Regulatory Affairs Department at INEOS ABS.

Typical Physical Properties* for Natural Resin	ASTM Test Method (Other)	Lustran® ABS LK 197 ABS Resin**	
		U.S. Conventional	SI Metric
General Specific Gravity Density Specific Volume Water Absorption, Immersion at 73°F (23°C): 24 Hours Melt Flow Rate at 230°C/10-kg Load Gloss, 60°, Sheet	D 792 D 792 D 792 D 570 D 1238 D 523	0.038 lb/in ³ 26.1 in ³ /lb	1.06 1.06 g/cm ³ 0.94 cm ³ /g 0.4 ^m % 9.2 g/10 min 90%
Mechanical Tensile Stress at Yield: 160°F (71°C) 73°F (23°C) 0°F (-18°C) Tensile Modulus: 160°F (71°C) 73°F (23°C) 0°F (-18°C) Flexural Stress at Yield: 160°F (71°C) 73°F (23°C) -40°F (-40°C) Flexural Modulus: 160°F (71°C) 73°F (23°C) -40°F (-40°C) Impact Strength, Notched Izod: 0.125-in (3.2-mm) Thickness 73°F (23°C) 0°F (-18°C) -40°F (-40°C) Instrumented Impact: ^a Peak Energy 73°F (23°C) 0°F (-18°C) -40°F (-40°C) Total Energy 73°F (23°C) 0°F (-18°C) -40°F (-40°C) Rockwell Hardness	D 638 D 638 D 790 D 790 D 256 D 3763 D 785	3,200 lb/in ² 5,800 lb/in ² 8,600 lb/in ² 220,000 lb/in ² 330,000 lb/in ² 370,000 lb/in ² 7,200 lb/in ² 9,200 lb/in ² 16,500 lb/in ² 280,000 lb/in ² 60,000 lb/in ² 400,000 lb/in ² 4.5 ft-lb/in 2.5 ft-lb/in 1.7 ft-lb/in 16 ft-lb 14 ft-lb 8 ft-lb 22 ft-lb 18 ft-lb 10 ft-lb	22.1 MPa 40.0 MPa 59.3 MPa 1.5 GPa 2.3 GPa 2.6 GPa 49.6 MPa 63.4 MPa 113.8 MPa 1.9 GPa 2.5 GPa 2.8 GPa 240 J/m 133 J/m 91 J/m 22 J 19 J 11 J 30 J 24 J 14 J 113 R Scale
Thermal Deflection Temperature Under Load: Unannealed, 264 psi (1.82 MPa) Unannealed, 66 psi (0.46 MPa) Annealed, 264 psi (1.82 MPa) Annealed, 66 psi (0.46 MPa) Coefficient of Linear Thermal Expansion Relative Temperature Index: 1.47-mm (0.058-in) Thickness Electrical Mechanical with Impact Mechanical without Impact	D 648 D 696 (UL746B)	185°F 199°F 201°F 214°F 5.0 E-05 in/in/°F	85°C 93°C 94°C 101°C 9.0 E-05 mm/mm/°C 60°C 60°C 60°C
Flammability*** UL94 Flame Class: 1.47-mm (0.058-in) Thickness Burn Rate: 3.2-mm (0.125-in) Thickness	(UL94) D 635		HB Rating 35.6 ^m mm/min

* These items are provided as general information only. They are approximate values and are not part of the product specifications.

** Properties tested in transverse direction (worst case) on 125-mil extruded sheet specimens with less than 10% orientation unless otherwise noted.

*** Flammability results are based on small-scale laboratory tests for purposes of relative comparison and are not intended to reflect the hazards presented by this or any other material under actual fire conditions.

^a 0.5-in dart, 3-in clamp, 7.6 mph.

^m Tested on injection molded specimen.

Note: The information contained in this publication is current as of October 2012. Please contact INEOS ABS to determine whether this publication has been revised.

The manner in which you use and the purpose to which you put and utilize our products, technical assistance and information (whether verbal, written or by way of production evaluations), including any suggested formulations and recommendations are beyond our control. Therefore, it is imperative that you test our products, technical assistance and information to determine to your own satisfaction whether they are suitable for your intended uses and applications. This application-specific analysis must at least include testing to determine suitability from a technical as well as health, safety, and environmental standpoint. Such testing has not necessarily been done by us. Unless we otherwise agree in writing, all products are sold strictly pursuant to the terms of our standard conditions of sale. All information and technical assistance is given without warranty or guarantee and is subject to change without notice. It is expressly understood and agreed that you assume and hereby expressly release us from all liability, in tort, contract or otherwise, incurred in connection with the use of our products, technical assistance, and information. Any statement or recommendation not contained herein is unauthorized and shall not bind us. Nothing herein shall be construed as a recommendation to use any product in conflict with patents covering any material or its use. No license is implied or in fact granted under the claims of any patent.

INEOS
ABS

INEOS ABS (USA) Corporation
INEOS ABS NAFTA
356 Three Rivers Parkway
Addyston, OH 45001

www.ineos-abs.com