

DOW CORNING[®] MB50-017 Masterbatch

FEATURES

- Imparts processing improvements and modified surface characteristics

BENEFITS

- Improved throughput
- Reduced energy consumption
- Enhanced scratch resistance
- Improved slip properties
- Reduced waste
- Enhanced stability vs. traditional processing aids and lubricants

COMPOSITION

- Free flowing solid pellets

Ultra-high molecular weight siloxane polymer dispersed in thermoplastic polyurethane.

APPLICATIONS

- An additive typically used in thermoplastic polyurethane compatible materials.

TYPICAL PROPERTIES

Specification Writers: These values are not intended for use in preparing specifications. Please contact your local Multibase sales office or your Global Multibase Connection before writing specifications on this product.

Test	Property	Unit	Result
	Appearance		Off-white pellets
	Siloxane Content	%	50
	Organic resin		TPU
	Suggested use level	%	0.1 to 5.0

DESCRIPTION

DOW CORNING MB50-017 Masterbatch is a pelletized formulation containing 50% of an ultra-high molecular (UHMW) Siloxane polymer dispersed in Thermoplastic Polyurethane (TPU). It is designed to be used as an additive in Thermoplastic Polyurethane (TPU) compatible systems to impart benefits such as processing improvements and modification of surface characteristics.

Liquid Siloxane plastic additives have been used for several years to improve the lubricity and flow of thermoplastics. They are effective in this although some difficulties have been experienced in the incorporation of liquids into thermoplastic melts without the use of specialized equipment. It has also been difficult to produce Masterbatches with greater than 20% liquid Siloxane because of processing difficulty and bleed problems.

The DOW CORNING MB Series Masterbatches address these problems

by supplying a high concentration of an ultra-high molecular weight (UHMW) Siloxane as a dispersion in a dry pellet form in a variety of thermoplastics.

HOW TO USE

DOW CORNING MB Series Masterbatches may be processed in the same way as the thermoplastics on which they are based. Sufficient DOW CORNING MB50-017 Masterbatch should be blended with virgin polymer pellets to give the desired Siloxane leveling the final product. DOW CORNING MB50-017 Masterbatch pellets can be added during compounding in a single screw extruder or added at the feed hopper during the injection molding or extrusion. Drying before use may be needed.

HANDLING

PRECAUTIONS

PRODUCT SAFETY INFORMATION REQUIRED FOR SAFE USE IS NOT INCLUDED. BEFORE HANDLING, READ PRODUCT AND SAFETY DATA SHEETS AND CONTAINER LABELS FOR SAFE USE, PHYSICAL AND HEALTH HAZARD INFORMATION. THE SAFETY DATA SHEETS IS AVAILABLE FROM YOUR LOCAL DOW CORNING SALES REPRESENTATIVE.

USABLE LIFE AND STORAGE

When stored at or below 35 degrees C (95 degrees F) in the original unopened containers DOW CORNING MB50-017 Masterbatch has a usable life of 48 months from the date of production.

PACKAGING INFORMATION

This product is available in a variety of container sizes. Contact your local Multibase sales representative for information about container sizes available in your area.

HEALTH AND ENVIRONMENTAL INFORMATION

To support Customers in their product safety needs, Multibase has an extensive Product Stewardship organization and a team of Product Safety and Regulatory Compliance (PS&RC) specialists available in each area.

For further information, please see our website, dowcorning.com or consult your local Multibase representative.

LIMITED WARRANTY INFORMATION – PLEASE READ CAREFULLY

The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our

products are beyond our control, this information should not be used in substitution for customer's tests to ensure that our products are safe, effective, and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe any patent.

Multibase's sole warranty is that our products will meet the sales specifications in effect at the time of shipment.

Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

MULTIBASE SPECIFICALLY DISCLAIMS ANY OTHER EXPRESS OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY.

MULTIBASE DISCLAIMS LIABILITY FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.

www.multibase.com

www.dowcorning.com